200	STAIRWAY ASSIST FOR INDIVIDUAL OR MINOR BARRIER (E.G., CURB) LIFT FOR IMPAIRED INDIVIDUAL	222	<pre>INDUSTRIAL LIFT TRUCK OR REQUIRED COMPONENT THEREOF (E.G., FORKLIFT)</pre>
201	.Mounted adjacent stairway for travel parallel thereto	223 224	.Having safety cutoff control .Having control for load support
202	Having specific means		drive-means
202	contacting or on load support	225	.Having foldable vertical guide
	for stopping thereof	226	.Having extensible vertical guide
203	STATIONARY LIFT FOR ROADWAY		for load support
	VEHICLE OR REQUIRED COMPONENT	227	Guide or drive-means therefor
	THEREOF		positioned to enhance operator
204	.With distinct jack on vehicle		visibility
	support	228	And guiding means for fluid
205	.With floor pit opening for		drive line
	support and safety cover	229	Extended by single fluid ram
	therefor	230	Specific vertical guide
206	.With safety prop or braking rod	231	.Having structure allowing
	for support		propulsion or steering by
207	.Having position lock for	232	<pre>walking attendantWith stabilizing outrigger</pre>
	engaging sustaining drive means or guide means of	232	with stabilizing outligger .Having specific drive-means for
	support	233	load support
208	Ratchet bar and latching pawl-	234	Including fluid ram
200	type lock	235	Including cable accumulating-
209	.With safety cutoff for drive		type drum
	means	236	Including gear and mating rack
210	.Having specific drive means for		or chain
	support	237	.Having specific load support
211	Includes plural sustaining		structure (e.g., forks)
	levers (e.g., Scissored	238	.Having specific guide means for
	levers)		load support
212	Powered by vehicle being lifted	239	MOUNTED ON EXTERIOR OF BUILDING
213	Includes driven sustaining	240	TRANSPORTABLE ELEVATOR
	columns on opposite sides of	241	.Nonself supporting-type (e.g.,
01.4	support	0.4.0	leaned against building)
214	Having threaded rider and mating screw	242	.Knockdown or collapsible for
215	Includes sustaining fluid ram	243	transportWheel supported
216	Having specific vehicle support	243	.Wheel supported .Wheel supported
210	structure (e.g., trackways)	245	INCLINED ELEVATOR
217	With movable stop engaging	246	.Having linking cable tension
	vehicle wheel	210	change actuated stopping means
218	Includes portion positioned or		for load support
	shaped to engage axle or	247	HAVING COMPUTER CONTROL OF
	undercarriage		ELEVATOR
219	Portion adjusts to plural use	248	.Includes redundant circuitry
	positions	249	HAVING INDEPENDENT SUPPORTS
220	Portion moves from use to		CARRYING DISTINCT LOADS AND
	nonuse configuration (e.g.,		SHARING COMMON PATH
0.01	alternate supports)	250	HAVING SPECIFIC LOAD SUPPORT
221	Includes auxiliary or	0.5-1	DRIVE-MEANS OR ITS CONTROL
	adjustably spaced trackway	251	.Includes linking support cable
			(e.g., rope, chain) in drive-
			means

187 - 2 CLASS 187 ELEVATOR, INDUSTRIAL LIFT TRUCK, OR STATIONARY LIFT FOR VEHICLE

252	And reciprocatingly shifted pulley wheel pulling thereon	282	Actuated by load support contacting trip in shaft
253	Shifted by fluid ram	283	Having trip at each of plural
254	And rotatably driven drum		landings
	pulling thereon	284	And means for final leveling
255	With projections or apertures	285	For fluid-type power source
	for engaging complementary	286	Actuated by load support
	formations on cable (e.g.,		speed sensor or governor
	sprocket)	287	Includes safety cut off switch
256	Plural driven drums		actuated by load support speed
257	Each moves distinct load		sensor or governor
	support	288	Control actuates mechanical
258	Having distinct drive motors	200	braking means for power source
259	Cable accumulating-type drums	289	For electric power source
260	Different size drums	290	
		290	With auxiliary supply of
261	Cable accumulating-type drum	001	electricity
262	Having cable guiding pulley	291	Having means for final
	wheel spaced therefrom		leveling
263	With structure adapting drum	292	With means for stopping
	for manual drive		vibration or bump start
264	With separate biasing means	293	Controls power source speed
	maintaining cable tension	294	Actuated near terminus of
265	Includes spring supported		shaft
	pulley	295	Having control signal
266	Having cable guiding pulley		pattern generator
	wheel spaced therefrom	296	Limited to power source
267	.Includes threaded rider mating		(i.e., motor) utilizing A.C.
	with support screw in drive-		power
	means	297	Limited to power source
268	Driven rider	271	(i.e., motor) utilizing D.C.
269	.Includes scissored supporting		power
200	levers in drive-means	298	Actuated by human operator
270		200	engaging specific input part
270	.Includes gear on support mating	299	
0.01	with stationary rack or chain	299	With means locking input
271	Worm-type gear		part of control against
272	.Includes fluid supporting ram in	200	movement
	drive-means	300	Actuated by presence of
273	Pneumatic (e.g., steam)		obstruction in shaft
274	Plural fluid rams having	301	Actuated by location of access
	interrelated operation		barrier or its lock
275	With fluid flow controlling	302	Actuated by load support
	means		contacting trip in shaft
276	.Includes control for power	303	Having trip at each of plural
	source of drive-means		landings
277	With specific electrical	304	Trip supported on or formed
	component		by cable
278	Actuated by movement of	305	Actuated by load support speed
270	building (e.g., seismic		sensor or governor
	activity)	306	Actuated by human operator
279	Actuated by presence of		engaging specific input part
ر ,	obstruction in shaft	307	With means for locking input
280		307	part of control against
∠ 0∪	Actuated by location of access barrier or its lock		movement by operator
201			movement by operator
281	Actuated by excessive load		

308	Actuated by position or	334	.Including slideably mounted
	movement of access barrier or		barrier on load support
	its position lock	335	With position lock therefor
309	Having barrier position lock	336	WITH CLOSURE MEANS FOR SHAFT
	operable only when load		OPENING THROUGH LANDING
	support or control input part	337	.Including pivoted closure
210	safely positioned	338	Shifted by drive-means powered
310	With common actuation of		by load support motion
	barrier position lock and	339	With closure latching means
211	input part locking means	340	.Including transversely sliding
311	Using cable to transmit input		closure
312	Running cable type	341	Shifted by drive-means powered
313	WITH BARRIER FOR REGULATING		by load support motion
214	ACCESS TO LOAD SUPPORT	342	.Including closure bodily carried
314	.Operation variable for		along shaft by load support
	emergency, maintenance, or	343	HAVING MEANS CUSHIONING CONTACT
215	abnormal condition		OF LOAD SUPPORT WITH TERMINUS
315	.Includes motor or motor driven		OF SHAFT
	linkage for shifting barrier	344	.Fluid resistance or shock
316	With specific electrical		absorber-type means
0.1.5	control therefor	345	HAVING FLUID DAMPENING MEANS
317	Includes object detecting		REGULATING LOAD SUPPORT
	sensor or switch on barrier		MOVEMENT
318	Shifts barrier mounted at	346	.With fluid coacting portion
	landing		carried by load support
319	Through coupling with barrier	347	.Includes piston and cylinder
	on load support		attached to support by cable
320	Plural interconnected motors	348	WITH EMERGENCY RUNNING SUSPENSION
320	shift barriers at different	348	WITH EMERGENCY RUNNING SUSPENSION CABLE FOR LOAD SUPPORT
	shift barriers at different landings	348 349	
320	<pre>shift barriers at different landingsMotor stationarily mounted and</pre>		CABLE FOR LOAD SUPPORT
	<pre>shift barriers at different landingsMotor stationarily mounted and linkable to barriers on</pre>	349	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS
321	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landings		CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE
	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft	349	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR
321	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landings	349	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD
321 322 323	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motor	349 350	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT
321	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load	349	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING
321 322 323 324	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support	349 350	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR
321 322 323	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at	349 350 351	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF
321 322 323 324 325	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landing	349 350	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating
321 322 323 324	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means	349350351352	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rack
321 322 323 324 325	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load	349 350 351 352 353	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear
321 322 323 324 325 326	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load support	349350351352	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier
321 322 323 324 325	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in	349 350 351 352 353 354	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movement
321 322 323 324 325 326	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-means	349 350 351 352 353	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact
321 322 323 324 325 326	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum	349 350 351 352 353 354 355	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support
321 322 323 324 325 326	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in	349 350 351 352 353 354	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having
321 322 323 324 325 326 327 328	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-means	349 350 351 352 353 354 355	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact
321 322 323 324 325 326	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding	349 350 351 352 353 354 355 356	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact component
321 322 323 324 325 326 327 328	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding pulley therefor in drive-means	349 350 351 352 353 354 355	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact componentMounted only at landings or
321 322 323 324 325 326 327 328	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding pulley therefor in drive-meansWith means to couple to barrier	349 350 351 352 353 354 355 356	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact componentMounted only at landings or terminus of shaft
321 322 323 324 325 326 327 328 329 330	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding pulley therefor in drive-meansWith means to couple to barrier on load support	349 350 351 352 353 354 355 356	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact componentMounted only at landings or terminus of shaftHaving drive-means for
321 322 323 324 325 326 327 328 329 330 331	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding pulley therefor in drive-meansWith means to couple to barrier on load supportWith position lock therefor	349 350 351 352 353 354 355 356	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact componentMounted only at landings or terminus of shaftHaving drive-means for component powered by load
321 322 323 324 325 326 327 328 329 330	shift barriers at different landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding pulley therefor in drive-meansWith means to couple to barrier on load support	349 350 351 352 353 354 355 356	CABLE FOR LOAD SUPPORT WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact componentMounted only at landings or terminus of shaftHaving drive-means for

187 - 4 CLASS 187 ELEVATOR, INDUSTRIAL LIFT TRUCK, OR STATIONARY LIFT FOR VEHICLE

359	.Includes movable contact component on support for	384	Having security or priority preemption feature
260	engaging shaft structure	385	Dispatches load supports from
360	Interlocking only with		designated landing
	structure of landings or terminus of shaft	386	Frequency based on interval of time
361	Actuated by change in	387	Assigns calls to load supports
	suspension or counterweight		on predetermined basis
	cable tension	200	-
260		388	.Also directs response
362	And shaped to cut into	389	.Includes specific floor selector
	cooperating structure	390	ALARM SYSTEM
363	And interlocking with	391	WITH MONITORING, SIGNALLING, AND
	complementary stationary		INDICATING MEANS
	formation (e.g., catches)	392	.Monitors passengers
364	Slidably mounted contact		
301		393	.Monitors operational parameter
265	component	394	Load support position
365	Slides perpendicular to path	395	HAVING CALL BUTTON WITH INDICATOR
	of support	396	GENERAL INFORMATION DISPLAY
366	Plural pivotally attached		(E.G., STORE DIRECTORIES)
	gripping contact components	397	WITH VISUAL INDICATOR OF MOVEMENT
	engaging common rail	391	
367	Pivotally attached contact		OF LOAD SUPPORT
307		398	.Indicates particular one of
260	component		plural load supports
368	With eccentric camming face		responding
369	Having similar contact	399	.Indicates existing location
	component cooperating to grip	400	WITH SAFETY OR SEALING MEANS FOR
	common rail	100	GAP BETWEEN LOAD SUPPORT AND
370	Plural gripping contact		LANDING
	components engaging common	407	
	rail	401	HAVING SPECIFIC LOAD SUPPORT
271			STRUCTURE OR ARRANGEMENT
371	Slidably mounted contact		(E.G., CAR FRAMING)
	component	402	.Arranged to carry masonry hod
372	Having wedge shape or sliding	403	.With means for engaging wheels
	along incline		of carried vehicle
373	Actuated by load support speed	404	HAVING SPECIFIC COUNTERBALANCE
	governor or sensor	404	
374	Pivotally attached contact		MEANS FOR LOAD SUPPORT
3/4		405	.Includes variable weight
	component	406	HAVING SPECIFIC STATIONARY
375	Plural gripping contact		GUIDING STRUCTURE FOR
	components engaging common		COUNTERBALANCE MEANS OR LOAD
	rail		SUPPORT
376	Slidable contact component	407	.Formed from cable
	having wedge shape or sliding		
	along incline	408	.And mounting means therefor
200		409	HAVING SPECIFIC GUIDE SHOE
377	Actuated by human operator	410	.With roller
378	And interlocking with	411	HAVING SPECIFIC FORCE
	complementary stationary		TRANSMITTING CONNECTION FOR
	formation		COUNTERWEIGHT OR LOAD SUPPORT
379	Pivotally attached contact	412	
	component	417	.Equalizes tension in, or length
380	WITH CALL REGISTRATION MEANS		of, plural linking cables
		413	HAVING SPECIFIC ARRANGEMENT OR
381	.Having call cancel or refuse		CONNECTION OF ELECTRICAL OR
	feature		FLUID SERVICE LINE
382	.Shared by plural load supports	414	MISCELLANEOUS
383	Assigns load supports to zones		

CROSS-REFERENCE ART COLLECTIONS

900	TEMPORARY CONSTRUCTION ELEVATOR
	FOR BUILDING
901	CONTROL MODIFIED FOR USE BY
	DISABLED INDIVIDUAL
902	CONTROL FOR DOUBLE-DECKER CAR

FOREIGN ART COLLECTIONS

FOR 000 CLASS-RELATED FOREIGN DOCUMENTS

187 - 6 CLASS 187 ELEVATOR, INDUSTRIAL LIFT TRUCK, OR STATIONARY LIFT FOR VEHICLE